




TECHNICAL SPECIFICATIONS

Sensor type	sCMOS
Sensor size	1/1.8"
Imaging area	8.92mm (Diagonal)
Capture resolution	6MP
Live display mode through USB	3072x2048, 1536x1024 pixels
Pixel size	2.4x2.4µm
Scan mode	Progressive
Shutter mode	Rolling Shutter
Data transfer	USB 3.1
Max. frames per second (fps*)	3072x2048 @ 30fps 1536x1024 @ 50fps
Exposure time	16 µsec to 2 sec
Operating temperature	From -10 to +60 Degrees Celsius non condensing
Sensitivity	425mV(G) @ 1/30 sec
Support device	TWAIN, SDK and DirectShow Driver
Supported OS	Microsoft Windows 7/8/10, MAC OSX10.9, Linux or higher
Minimum computer requirements	2GHz dualcore - RAM memory 2GB - Video memory min. 512 MB
Lens mount	C-Mount
Software	MiImages Plus 3.0 for Windows, OSX and Linux
Functions	Still image and video capture, live and still image measurement, image adjustments, white balance, automatic & manual exposure, individual objective calibration system.
Power supply	5V (from USB Port)
Package includes	CS ring adaptor, USB 3.1 cable, MIP-dot calibration slide, MiImages Plus 3.0 for PC/OSX/Linux

*Frames per second under optimal lighting conditions and in compliance with computer technical requirements.



Medimage Technologies Pvt. Ltd.

3A, Type II, I.E., Kukatpally, Hyderabad (A.P), India - 500 072

Ph: 91-040-23075680

Fax: 91-040-23070848

Email: info@metavis.com

Web: www.metavis.com

FAST FRAME RATES

sCMOS SENSOR

USB 3.1 INTERFACE

MIP 3.0 SOFTWARE