

P 200

Binocular
Pathological
Microscope





TECHNICAL SPECIFICATIONS

Binocular Observation Head

- Siedentopf Observation head inclined at 30° rotatable at 360°.
- Diopter adjustment ring on ocular tube. (± 5).
- Inter-pupillary distance from 55mm to 75mm.

Eyepiece (Anti fungus coated)

- Wide Field 10X (paired) F.O.V 18mm.

Objectives (Anti fungus coated)

- S-Plan Achromatic 4X
- S-Plan Achromatic 10X
- S-Plan Achromatic 40X(S.L.)
- S-Plan Achromatic 100X Oil(S.L.)

Mechanical Body

- Co-axial focusing system. PRE-FOCUSING LEVER & TENSION ADJUSTMENT RING.
- The slow motion has 1Div=0.002mm.
- Quadruple nosepiece revolves on ball bearing.
- Double plate mechanical stage size 140mmX155mm having low positioned co-axial controls on ball bearing
- Cross movement 55mm X 75mm.

Sub Stage Condenser

- Abbe condenser N.A.1.25 swing out filter holder, iris diaphragm.

Illumination System

- Built-in-base illumination system with 3W LED bulb and adjustable brightness.

Standard Accessories

- Dust cover, operating manual, guarantee card, blue filter and Styrofoam molded pack.



Medimage Technologies Pvt. Ltd.

3A, Type II, I.E., Kukatpally, Hyderabad (A.P), India - 500 072

Ph: 91-040-23075680

Fax: 91-040-23070848

Email: info@metavis.com

Web: www.metavis.com